## U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

## MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

		ng (29 CFR 1915, 191	0, 15171	
· · · · · · · · · · · · · · · · · · ·	SEC	TION I	Barrier Contract	V
MANUFACTURER'S NAME			EMERGERY Y LELEPHO	धीर्वे ह
Flamort Chemical Company				
ADDRESS (Number, Street, City, State, and ZIP C 746 Natoma St. San Franci	isco, CA 9	4103		1
CHEMICAL NAME AND SYNONYMS		TRADE NA	ME AND SYNONYMS	THE OWNER A STREET
CHEMICAL FAMILY		FORMULA FLAMO	<u>-t_T                                    </u>	<del></del>
Water soluble bromine and r	nitrogen	<u> </u>		741 773
	VII - HAZA	RDOUS INGREDIE	NTS (PAL)	<del></del>
PAINTS, PRESERVATIVES, & SOLVENTS	% TLV (Units)	ALLOYS AND M	ETALLIC COATINGS	X TLV
PIGMENTS		BASE METAL		
CATALYST N/A		ALLOYS	p. 1	8 2 7 4 2 7
VEHICLE		METALLIC COATING	Section 1	1. 1
SOLVENTS	ngan ga a an a magasanan	FILLER METAL PLUS COATING OR C	OREFLIN	no and a department
ADDITIVES		OTHERS	10	Byr y dage ve y na i flygriffe fregering
OTHERS				
HAZARDOUS MIXTURE	S OF OTHER LI	QUIDS, SOLIDS, OR GA	SES	TL\
	<del></del>			
N/A	·- <u>-</u>			<del>                                     </del>
		ı,		<u> </u>
	· · · · · · · · · · · · · · · · · · ·	• • • • • • • • • • • • • • • • • • • •	*	
· SF(	CTION III .	PHYSICAL DATA	1. i was	NA TOWNSON SEC
BOILING POINT (°F.) £12F, 100C		SPECIFIC GRAVITY		4 . 41 2017000000
VAPOR PRESSURE (mm Hg.) Same as wa	ter	PERCENT, VOLATILE		
VAPOR DENSITY (AIR=1) N/A-		BY VOLUME (%) EVAPORATION RATE		i i Gest
SOLUBILITY IN WATER Soluble in wa		-1)	<u></u>	
DOIGDIG IN WA			The second of th	
APPEARANCE AND ODOR Clear solut	TOD, SI AMI	ionla odor		
SECTION IV -	FIRE AND	EXPLOSION HAZA	RD DATA	The Marketter
FLASH POINT (Method used) N/A		FLAMMABLE LIM		Uel
EXTINGUISHING MEDIA. N/A	•	्रा १६ तल्झ चराव		MIT JUNEAN
SPECIAL FIRE SIGUEING PROCESSIONS	/A		The second of th	A design to the second
	<i>y</i>		A CONTRACTOR OF THE PROPERTY O	STANIA TENENTERIO
UNUSUAL FIRE AND EXPLOSION HAZARDS	N/A		and the state of t	en i en
•			ر د سواس د د د د د د د د د د د د د د د د د د د	

PAGE (1)

(Continued on reverse side)

Form OSHA-20 Rev. May 72

	Not establis	hed			
FFECTS OF OVEREXPOSURE	NOC 63 CADITIS	illeri	<del></del>		
			٠.		
MERGENCY AND FIRST AID P	ROCEDURES				
MERGENCY AND FIRST AID P	Skin: Wash	off in flowing	water or	shower	
, , , , , , , , , , , , , , , , , , ,	Eyes: Wash	with water for	at least	5 minutes	<u> </u>
<del></del>					ingested

			SECTION	ON VI - RE	ACTIVITY DATA
STABILITY	UNS	TABLE		CONDITIONS	
INCOMPATABILI	STABLE		x	N//	
HAZARDOUS DE	COMPOSI	TION PROD	LICTS	berates br	dizing material.  comine or HBR or Cyanides and cyanates
HAZARDOUS POLYMERIZATION		MAY OCCUR			conditions to avoid wider extreme high temp.
· va·memen	,,,	WILL NOT OCCUR		х	

·	SECTION VII - SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE	MATERIAL IS RELEASED OR SPILLED
in accordance with	local, State and Federal regulations.
	rocal, State and rederal regulations.
WASTE DISPOSAL METHOD	
WASTE DISPOSAL METHOD	Dissolve in water and flush with plenty of water if permittee
	i point of e
by applicable dis	posal regulations.

	SECTION VIII - SPECIA	PROTECTION INFORMATION	
RESPIRATORY PR	OTECTION (Specify type)		
VENTILATION	LOCAL EXHAUST Good room ve		d dust/mist respir
	MECHANICAL (General)	OTHER	
PROTECTIVE GLO	Recommended	Safety glasses	

	<del></del>					
	SECTION	IX - SPECIAL	PRECAUTI	ONS		
PRECAUTIONS TO BE Practice	PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Practice reasonable care and caution. Store in coal, dry area.					
OTHER PRECAUTIONS	•				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
OTHER PRECAUTIONS	•	·			-	
					a transfer of the	

) PAGE (2)

\$U.S. G.P.O. 1983-381-271/231

Form OSHA-20